

Comprehensive

Safety & Storage Cabinets



Why do I need a safety cabinet?

One of the leading causes of industrial fires is the improper storage and handling of flammable liquids. Safety cabinets help you safely store fuels, chemicals, and solvents to reduce the risk of fire and protect your people and property.

Safety cabinets serve critical functions:

- Improve awareness—high-visibility cabinet color and prominent labeling identify potentially hazardous chemicals
- Keep dangerous liquids safely organized and segregated—for indoor use
- Increase maximum allowable quantities of flammable and combustible liquids in control areas
- Improve efficiency by locating materials near point-of-use
- Improve security with locking mechanism
- Ensure safe evacuation time in the event of a fire
- Provide compliance with federal OSHA regulations and the National Fire Protection Association

Approvals and Compliance

Each Justrite steel safety cabinet meets at least one or more of the following regulations:

- OSHA 1910.106
- National Fire Protection Association (NFPA) Flammable Liquid Code 30
- NFPA Fire Code 1
- International Fire Code (IFC)
- National Fire Code of Canada
- NFPA Hazardous Materials Code 400
- European EN standard 14470-1 and 14727

Most cabinets carry independent, third-party approval:

- FM Approvals
- MPA Dresden



Considerations when selecting a safety cabinet

- Federal, state, and local compliance requirements
- Size and type of container being stored
- Capacity needed
- Type of chemical being stored
- Security and safety features such as U-Loc™ padlockable handle, SpillSlope® shelves, Haz-Alert™ warning labels, all welded construction

10 Year
Limited Warranty



8 Safety & Storage Cabinets

Sure-Grip® EX safety storage cabinets offer top performance for indoor flammable liquid storage and protection.

Fusible links hold doors wide open and melt at 165 F (74 C) for automatic closure (on self-closing models).

Sturdy 18-gauge (1-mm) double wall steel construction with 1-1/2-in (38-mm) of insulating air space.

Easy-close, self-latching doors; U-Loc™ handle (shown below) does not require manual rotation to engage mandatory three-point latch.

Fully welded, not riveted, construction holds squareness for longer life and offers greater protection in a fire since air gaps are reduced.

Continuous piano hinge provides smooth closure.

Durable and chemical-resistant, lead-free powder-coat paint finish, inside and out, retains high gloss look and minimizes the effects of corrosion and humidity.

Dual vents with built-in flash arresters strategically placed at bottom and opposite top.




Concealed self-close mechanism provides obstruction-free access to top shelf space. Self-indexing doors guarantee they will close in sequence and ensure a tight closure from top to bottom (on self-closing models). **Patented.**

Patented SpillSlope® safety shelves direct spills to back and bottom of leakproof sump. Adjustable on 3-in (76-mm) centers, they meet ANSI standards with a 350-lb (159-kg) safe allowable load.

Welded shelf hangers interlock with shelf to offer maximum stability with no flimsy brackets to lose.

2-in (51-mm) leakproof containment sump holds leaks and meets EPA requirements.


45-gal (170-L) self-close door style



Stainless steel, 3-point bullet self-latching system provides fail-safe, positive door closure with increased heat resistance.



Complies with OSHA 29 CFR 1910.106 and NFPA Code 30, section 9.5.3



Adjustable leveling feet support cabinets on uneven surfaces.



U-Loc™ handle includes double key set or can be padlocked (not included) for greater security.



SpillSlope® safety shelves direct spills to back and bottom of leakproof sump. Meets ANSI MH28.1



Welded construction holds squareness for long life; door astragal provides extra sturdiness.



Highly visible HazAlert™ reflective label provides warning—"Flammable – Keep Fire Away" in English, Spanish, and French.



Built-in grounding connector Shown with optional ground wire 08500.

Sure-Grip® EX Classic Safety Cabinets

Protect workers, reduce fire risks, and improve productivity by storing flammable fuels and chemicals in OSHA- and NFPA-compliant safety cabinets

- Independently fire tested and approved by FM Approvals
- 18-gauge (1-mm) thick double-wall, welded steel with 1-1/2-in (38-mm) of insulating air space.
- Adjustable, patented SpillSlope® galvanized steel shelves direct spills to back and bottom of 2-in (51-mm) leakproof sump
- 3-point stainless steel bullet latching system
- Self-closing models feature a fusible link that holds doors open—in fire conditions it melts at 165 F (74 C) for automatic closure. Concealed mechanism offers obstruction-free access to contents.
- U-Loc™ handle with two keys—accepts optional padlock
- Trilingual warning with Haz-Alert™ reflective labels
- Includes dual vents with flame arresters, adjustable leveling feet, and grounding connector



Complies with OSHA and provides 10 minutes of evacuation time.



Capacity Gal/L	Doors and Style	H x W x D	Shelves	Approv/Lstg Regulation	Model	CA Prop 65
30/114	2 door, manual	44 x 43 x 18 in	1	FM, N, O, A	893000	
	2 door, self-close	1118 x 1092 x 457 mm		FM, N, O, A, I	893020	⚠
45/170	2 door, manual	65 x 43 x 18 in	2	FM, N, O, A	894500	
	2 door, self-close	1651 x 1092 x 457 mm		FM, N, O, A, I	894520	⚠
60/227	2 door, manual	65 x 34 x 34 in		FM, N, O, A	896000	
	2 door, self-close	1651 x 864 x 864 mm		FM, N, O, A, I	896020	⚠
90/341*	2 door, manual	65 x 43 x 34 in	FM, N, O, A	899000		
	2 door, self-close	1651 x 1092 x 864 mm	FM, N, O, A, I	899020	⚠	

*OSHA 29CFR 1910.106(d)(3) states that not more than 60 gallons (227 L) of Category 1, 2, or 3 flammable liquids, nor more than 120 gallons (454 L) of Category 4 flammable liquids may be stored in a safety cabinet.

Accessories	Fits Cabinet Styles	W x D	Model
SpillSlope® steel shelf	30 & 45 gallon (114 & 170 L) - 43 in W (1092 mm)	39.375 x 14 in (1000 x 356 mm)	29937
	30 gallon (114 L) - 36 in W (914 mm)	32.375 x 20 in (822 x 508 mm)	29942
	60 gallon (227 L) - 34 in W (864 mm)	30.375 x 29 in (771 x 737 mm)	29944
	90 gallon (341 L) - 43 in W (1092 mm)	39.375 x 29 in (1000 x 737 mm)	29945

⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

10 Safety & Storage Cabinets

Sure-Grip® EX Safety Cabinets – Optional Colors

Same benefits like Sure-Grip® EX classic yellow cabinets, in 3 different colors for color-coding convenience

- Differentiate different types of liquids
- Segregate incompatible liquids
- Quick visual reference for workers



893001



893003



893005

Capacity Gal/L	Doors and Style	Exterior H x W x D	Shelves	Approv/Lstg Regulation	Red Model	Gray Model	White Model	CA Prop 65
30/114	2 door, manual	44 x 43 x 18 in	1	FM, N, O, A	893001	893003	893005	
	2 door, self-close	1118 x 1092 x 457 mm		FM, N, O, A, I	893021	893023	893025	⚠
	2 door, manual	35 x 36 x 24 in 889 x 914 x 610 mm		FM, N, O, A	893301	893303	893305	
45/170	2 door, manual	65 x 43 x 18 in	2	FM, N, O, A	894501	894503	894505	
	2 door, self-close	1651 x 1092 x 457 mm		FM, N, O, A, I	894521	894523	894525	⚠
60/227	2 door, manual	65 x 34 x 34 in		FM, N, O, A	896001	896003	896005	
	2 door, self-close	1651 x 864 x 864 mm		FM, N, O, A, I	896021	896023	896025	⚠
90/341*	2 door, manual	65 x 43 x 34 in	FM, N, O, A	899001	899003	899005		
	2 door, self-close	1651 x 1092 x 864 mm	FM, N, O, A, I	899021	899023	899025	⚠	

*OSHA 29CFR 1910.106(d)(3) states that not more than 60 gallons (227 L) of Category 1, 2, or 3 flammable liquids, nor more than 120 gallons (454 L) of Category 4 flammable liquids may be stored in a safety cabinet.

Sure-Grip® EX Safety Cabinets – Single Door

Full size, full storage capacity safety cabinets with a unique single-door design

- Same benefits of Sure-Grip® EX classic cabinets, but with a bifold, sliding single door that self-latches and self-closes
- Fusible link holds door open and automatically closes it under fire conditions
- Heavy-duty steel dual-track guidance system ensures smooth closure



893080

Capacity Gal/L	Doors and Style	Exterior H x W x D	Shelves	Approv/Lstg Regulation	Yellow Model	Red Model	Gray Model	White Model	CA Prop 65
30/114	1 bi-fold sliding self-close	44 x 43 x 18 in 1118 x 1092 x 457 mm	1	FM, N, O, A, I	893080	—	—	—	⚠
45/170	1 bi-fold sliding, self-close	65 x 43 x 18 in 1651 x 1092 x 457 mm	2		894580	894581	—	—	⚠
60/227	1 bi-fold sliding, self-close	65 x 34 x 34 in 1651 x 864 x 864 mm			896080	896081	—	—	⚠
90/341*	1 bi-fold sliding, self-close	65 x 43 x 34 in 1651 x 1092 x 864 mm	899080		—	—	—	⚠	

*OSHA 29CFR 1910.106(d)(3) states that not more than 60 gallons (227 L) of Category 1, 2, or 3 flammable liquids, nor more than 120 gallons (454 L) of Category 4 flammable liquids may be stored in a safety cabinet.

⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



Colors to organize your storage.

Sure-Grip® EX Slimline Safety Cabinets

Safely store flammables when floor space is tight or use to expand storage alongside existing cabinets

- Fire tested and approved by FM Approvals; complies with OSHA and NFPA
- 18-gauge (1-mm) thick double-wall, welded steel with 1-1/2-in (38-mm) of insulating air space
- 3-point stainless steel bullet latching system
- U-Loc™ handle with two keys—accepts optional padlock
- Adjustable, patented SpillSlope® galvanized steel shelves direct spills to 2-in (51-mm) leakproof sump
- Trilingual warning with Haz-Alert™ reflective labels
- Includes dual vents with flame arresters, adjustable leveling feet, grounding connector
- Self-closing models equipped with fusible link holds door open during use and melts at 165 F (74 C) to automatically close under fire conditions



Capacity Gal/L	Doors and Style	Exterior H x W x D	Shelves	Approv/Lstg Regulation	Yellow Model	Red Model	Gray Model	White Model	CA Prop 65
22/83 (standard)	1 door, manual	65 x 23.25 x 18 in 1651 x 591 x 457 mm	3	FM, N, O, A	892200	892201	892203	892205	
	1 door, self-close			FM, N, O, A, I	892220	892221	892223	892225	⚠
54/204 (deep)	1 door, manual	65 x 23.25 x 34 in 1651 x 591 x 864 mm		FM, N, O, A	895400	895401	895403	895405	
	1 door, self-close			FM, N, O, A, I	895420	895421	895423	895425	⚠

Accessories	Fits Cabinet Styles	W x D	Model
SpillSlope® steel shelf	22 gallon (83 L) slimline	19.625 x 14 in (498 x 356 mm)	29936
	54 gallon (204 L) deep slimline	19.625 x 29 in (498 x 737 mm)	29941

⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

12 Safety & Storage Cabinets

Sure-Grip® EX Piggyback Safety Cabinets

Low-height design allows you to store flammables on bench tops or on top of 30- or 45-gallon (114- and 170-L) cabinets

- Expand storage and safety segregate liquids
- Complies with OSHA and NFPA, FM-approved
- All welded, double-walled 18-gauge (1-mm) steel with 1-1/2-in (38-mm) of insulating air space
- Failsafe, 3-point stainless steel bullet latching system
- Leakproof 2-in (51-mm) sump captures spills
- U-Loc™ handle with two keys—accepts optional padlock
- Trilingual warning with Haz-Alert™ reflective labels
- Includes dual vents with flame arresters, adjustable leveling feet, grounding connector
- Self-closing models equipped with fusible link holds doors open during use and melts at 165 F (74 C) to automatically close under fire conditions
- Wall mount with optional wall hanger assembly, no. 25950



Piggyback cabinets can be stacked for better organization.



Capacity Gal/L	Number of and Style	Exterior H x W x D	Shelves	Approv/Lstg Regulation	Yellow Model	Red Model	Gray Model	White Model	CA Prop 65
12/45	2 door, manual	18 x 43 x 18 in	0	FM, N, O, A	891300	891301	891303	891305	
	2 door, self-close	457 x 1092 x 457 mm		FM, N, O, A, I	891320	891321	891323	891325	⚠
17/64	2 door, manual	24 x 43 x 18 in	1	FM, N, O, A	891700	891701	891703	891705	
	2 door, self-close	610 x 1092 x 457 mm		FM, N, O, A, I	891720	891721	891723	891725	⚠

Extra Accessories	Fits Cabinet Styles	Dimensions W x D	Model
SpillSlope® steel shelf	17 Gallon (64 L) piggyback	39.375 x 14 in (1000 x 356 mm)	29937
Wall mount kit	12 & 17 Gallon (45 L & 64 L) piggyback cabinets	—	25950

⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Sure-Grip® EX Countertop Safety Cabinets

- Compliant, compact design offers same fire protection of larger Justrite cabinets
- Use on workbenches for access to often-used liquids
- Door self-latches for secure closure. Self-close style also automatically closes when fusible link melts under fire conditions.
- Save space by mounting on wall with optional wall hanger assembly no. 25951



890400



Place cabinets near points-of-use to save time.

Capacity Gal/L	Number of Doors and Style	Exterior H x W x D	Shelves	Approv/Lstg Regulation	Yellow Model No	Red Model No	Gray Model No	White Model No	CA Prop 65
4/15	countertop; 1 door, manual	22 x 17 x 17 in 559 x 432 x 432 mm	1	N, O, A	890400	890401	890403	890405	
	countertop; 1 door self-close			N, O, A, I	890420	890421	890423	890425	⚠

Accessories	Fits Cabinet Styles	W x D	Model
SpillSlope® steel shelf	4 gallon (15 L) cabinet	13.375 x 13 in (340 x 330 mm)	29935
Wall hanger mount kit		—	25951

Sure-Grip® EX Compac Safety Cabinets

- FM-approved, complies with OSHA and NFPA for storage of flammables
- Fire-resistant design includes double-walled steel with 1-1/2-in (38-mm) of insulating air space and 3-point stainless steel bullet latch for positive, failsafe door closure
- Adjustable SpillSlope® safety shelf directs spills to leakproof 2-in (51-mm) sump
- Dual vents with flame arresters, leveling feet, and grounding connector
- 12-gal (45-L) cabinets at 35-in (889-mm) high fits under most workbenches



891200



Capacity Gal/L	Doors and Style	Exterior H x W x D	Shelves	Approv/Lstg Regulation	Yellow Model	Red Model	Gray Model	White Model	CA Prop 65
12/45	compac; 1 door manual	35 x 23.25 x 18 in 889 x 591 x 457 mm	1	FM, N, O, A	891200	891201	891203	891205	
	compac; 1 door self-close			FM, N, O, A, I	891220	891221	891223	891225	⚠
15/57	compac; 1 door manual	44 x 23.25 x 18 in 1118 x 591 x 457 mm		FM, N, O, A	891500	891501	891503	891505	
	compac; 1 door self-close			FM, N, O, A, I	891520	891521	891523	891525	⚠

Accessories	Fits Cabinet Styles	W x D	Model
SpillSlope® steel shelf	12 & 15 gallon (45 L & 57 L) cabinets	19.625 x 14 in (498 x 356 mm)	29936

⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

14 Safety & Storage Cabinets

Mini Safety Cabinet

- Small footprint cabinet safely stores flammables within close reach—relocates easily
- Three bungee cords keep contents in place when transporting around shop floor
- Adjustable shelf maximizes cabinet space
- Complies with OSHA and NFPA



890200



Easily transport cabinet to locations throughout your facility.

Capacity Gal/L	Doors and Style	Exterior H x W x D	Shelves	Approv/Lstg Regulation	Model
Aerosols	mini; 1 door, manual	22 x 17 x 8 in 559 x 432 x 203 mm	1	N, O, A	890200

Aerosol Can Benchtop Safety Cabinet

- OSHA- and NFPA-compliant compact cabinet offers hassle-free organization of aerosol cans anywhere
- Fits up to 24 cans in two steel roll-out shelves with easy glide plastic rollers and top guard protection
- Each shelf comes with an insert that holds twelve 2-3/4-in (70-mm) diameter x 10-in (254-mm) tall aerosol cans



890500



Shelves roll out for easy access.

Capacity	Exterior H x W x D	Roll-out Shelves	Approv/Lstg Regulation	Model
24 cans	27 x 21 x 18 in 686 x 533 x 457 mm	2	N, O, A	890500

Sure-Grip® EX Undercounter Safety Cabinets

Position a safety cabinet under a counter to take advantage of storage space and keep liquids near benchtop work space

- Recessed toe kick improves ergonomics by allowing user to stand closer to work surface
- Dual back wall vents with flame arrester permit venting if needed
- Fire-resistant, leakproof design with 3-point bullet latch for failsafe closure
- SpillSlope® shelf directs spills to back and down to sump
- OSHA- and NFPA-compliant, FM-approved



Conveniently locate liquids near work areas.

Capacity Gal/L	Doors and Style	Exterior H x W x D	Shelves	Approv/Lstg Regulation	Yellow Model	Red Model	Gray Model	White Model	CA Prop 65
22/83	2 door, manual	35 x 35 x 22 in	1	FM, N, O, A	892300	892301	892303	892305	
	2 door, self-close	889 x 889 x 559 mm		FM, N, O, A, I	892320	892321	892323	892325	⚠

Accessories	Fits Cabinet Styles	W x D	Model
SpillSlope® steel shelf	22 gallon (83 L) undercounter cabinet	31.56 x 18 in (802 x 457 mm)	29939

Sure-Grip® EX Wall-Mount Safety Cabinets

Make the most of usable storage space—hang cabinet above workbench for easy access to work solvents

- Fully compliant, fire-resistant design like larger Justrite safety cabinets
- Eye-level positioning allows easy access to often-used liquids
- Comes complete with mounting hardware

Capacity Gal/L	Doors and Style	Exterior H x W x D	Shelves	Approv/Lstg Regulation	Model
17/64	2 door, manual	24 x 43 x 18 in 610 x 1092 x 457 mm	1	N, O, A	8917008
20/76		44 x 43 x 12 in 1118 x 1092 x 305 mm	3	FM, N, O, A	893400

Accessories	Fits Cabinet Styles	W x D	Model
SpillSlope® steel shelf	17 gallon (64 L) wall mount cabinet	39.375 x 14 in (1000 x 356 mm)	29937
	20 gallon (76 L) wall mount cabinet	39.375 x 8.625 in (1000 x 219 mm)	29938



⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Sure-Grip® EX Safety Cabinet and Can Combo Package

Combination package of a safety cabinet with six safety cans—perfect for equipping a new facility with popular flammable storage products

- Cabinet meets OSHA and NFPA, FM-approved
- Type I cans also meet federal regulations, are accepted under CARB, and independently tested and approved by FM Approvals, UL listed in the U.S. and Canada, and are certified by TUV Technical Inspection Certification



8930208



8945008

Capacity Gal/L	Doors and Style	Exterior H x W x D	Cabinet and Can Number	Approv/Lstg Regulation	Model	CA Prop 65
30/114	2 door, manual-close	44 x 43 x 18 in 1118 x 1092 x 457 mm	893000 cabinet with six 7150100 cans	FM, N, O, A	8930008	
	2 door, self-close		893020 cabinet with six 7150100 cans	FM, N, O, A, I	8930208	⚠
45/170	2 door, manual-close	65 x 43 x 18 in 1651 x 1092 x 457 mm	894500 cabinet with nine 7150100 cans	FM, N, O, A	8945008	
	2 door, self-close		894520 cabinet with nine 7150100 cans	FM, N, O, A, I	8945208	⚠

Sure-Grip® EX High Security Cabinets

Use in environments requiring increased security against unauthorized access of flammable liquids

- Fully compliant fire-resistant design, FM-approved
- High visibility steel crossbar across both doors with sidebars offer double layer steel strength, deters prying
- Side bars accept padlocks (not included) for increased security
- Includes two shelves; blue and green cabinet also include a poly liner for shelves and sump to protect against corrosion
- For correctional facilities, site trailers, and schools



Capacity Gal/L	Color	Label	Exterior H x W x D	Shelves	Approv/Lstg Regulation	Manual Close Model	Self-Close Model	CA Prop 65
45/170	yellow	flammable	65 x 43 x 18 in 1651 x 1092 x 457 mm	2	FM, N, O, A	29884Y	SC29884Y	⚠
	red	flammable				29884R	SC29884R	⚠
	green	pesticide				29884P	SC29884P	⚠
	blue	acid				29884B	SC29884B	⚠

Accessories	Fits Cabinet Styles	W x D	Model
SpillSlope® steel shelf	30 & 45 gallon — 43 in W (1092 mm)	39.375 x 14 in (1000 x 356 mm)	29937
Replacement security bar, red	45 gallon	2 x 0.25 in (51 x 6 mm)	50961R
Replacement security bar, yellow	45 gallon	2 x 0.25 in (51 x 6 mm)	50962Y
Set of two No. 5 Master Locks®			50963A

Master Lock® is a registered trademark of Master Lock Co.

⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



90-Minute EN Safety Storage Cabinets

Extreme fire resistance for high-risk environments such as high occupancy sites, high-value/high asset settings, or remote areas that lack fire-fighting services

- Steel exterior with multiple layers of fire-resistant gypsum and mineral fiber insulation
- Intumescent strips expand to seal gaps in case of fire
- Hybrid-close door—manual close doors stop in any position, but self-close at 122 F (50 C) under fire conditions
- Independent cylinder locks on each door with locking state indicator
- Two top vents with butterfly valve close automatically at 158 F (70 C) in a fire
- Removable sump with perforated insert captures spills—keeps containers elevated to stay dry
- Transport base accepts pallet jack to move empty cabinet—accepts optional, removable base cover
- Meets EN, OSHA, NFPA and approved by FM Approvals and MPA Dresden



Ninety-minutes of fire protection provides high level of safety when point-of-use storage is required.



22605



22607 with optional base cover 22637

Powered by **asecos**[®]

Fire Rating (Minutes)	Capacity Gal/L (5 Gallon Can)	Maximum Capacity* (1 Liter Bottle)	Doors and Style	Exterior H x W x D	Shelves	Approv/Lstg Regulation	Model
90	30/114	168	2 door, hybrid-close	76.89 x 35.16 x 24.21 in (1953 x 893 x 615 mm)	3	FM, EN, N, O, A	22605
	45/170	264		76.89 x 46.97 x 24.21 in (1953 x 1193 x 615 mm)			22607

*Achieved through the use of additional shelves, maximum capacity is an estimate and may vary depending upon container size. Check with local authority for maximum allowable quantity restrictions.

18 Safety & Storage Cabinets



Position single-door extreme fire resistance cabinets where space is limited. Add a second cabinet if storage needs increase.



30-Minute EN Safety Storage Cabinets

Safely store flammables—30 minutes of fire protection extends evacuation time

- Meets EN, OSHA, NFPA and approved by FM Approvals and MPA Dresden
- Two-toned yellow body of melamine resin and flame retardant plates, with a steel door covered by textured, power-coat finish
- Intumescent protection strips expand and seal gaps between the door(s) and frame
- Hybrid-close door(s)—manually close and stops in any position, but self-close at 122 F (50 C) under fire conditions
- Independent cylinder locks on doors with locking state indicator
- Air vents close at 158 F (70 C) in event of a fire
- Removable sump with perforated insert captures spills—keeps containers elevated to stay dry
- Transport base accepts pallet jack to move empty cabinet—accepts optional, removable base cover



22601



22603 with optional base cover 22635




22632



22631



22633



22634



22638

Fire Rating (Minutes)	Capacity Gal/L (5 Gallon Can)	Maximum Capacity* (1 Liter Bottle)	Doors and Style	Exterior H x W x D	Shelves	Approv/Lstg Regulation	Model
30	30/114	168	1 door, hybrid-close	76.65 x 34.02 x 24.41 in (1947 x 864 x 620 mm)	3	FM, EN, N, O, A	22601
	45/170	264	2 door, hybrid-close	76.65 x 45.83 x 24.41 in (1947 x 1164 x 620 mm)			22603

*Achieved through the use of additional shelves, maximum capacity is an estimate and may vary depending upon container size. Check with local authority for maximum allowable quantity restrictions.

Accessories	Fits Cabinet Styles	Dimensions	Model
Steel shelf, powder-coated	30 and 90 minute - 30 gallon (114 L)	W x D: 29.21 x 17.3 in (742 x 435 mm)	22630
	30 and 90 minute - 45 gallon (170 L)	W x D: 41.02 x 17.3 in (1042 x 435 mm)	22631
Polypropylene tray	30 and 90 minute - 30 gallon (114 L)	H x W x D: 3.47 x 29.13 x 17.09 in (88 x 740 x 434 mm)	22632
Polyethylene tray	30 and 90 minute - 45 gallon (170 L)	H x W x D: 1.97 x 40.95 x 16.93 in (50 x 1040 x 430 mm)	22633
Base cover	30 minute - 30 gallon (114 L)	H x W: 3.43 x 30.95 in (87 x 786 mm)	22634
	30 minute - 45 gallon (170 L)	H x W: 3.43 x 42.76 in (87 x 1086 mm)	22635
	90 minute - 30 gallon (114 L)	H x W: 3.35 x 32.21 in (85 x 818 mm)	22636
	90 minute - 45 gallon (170 L)	H x W: 3.35 x 44.02 in (85 x 1118 mm)	22637
Cabinet mover - Set of 2	30 and 90 minute - 30 & 45 gallon (114 & 170 L)	H x W x D: 3.54 x 5.51 x 23.62 in (90 x 140 x 600 mm)	22638

Sure-Grip® EX Under Fume Hood Safety Cabinets

Fully compliant, designed for safe storage of solvents and flammable in laboratories

- Fits under fume hoods, benches, and counters—with ergonomic 4-in (102-mm) high x 3-in (77-mm) deep toe kick for standing close, less leaning
- 35-3/4-in (908-mm) height includes leg levelers installed and extended 5/8-in (15.9-mm)
- Welded, 18-gauge (1-mm) steel double-wall with 1-1/2-in (38-mm) insulating air space
- SpillSlope® shelf directs spills into 2-in (51-mm) leakproof sump
- Durable power-coat finish
- Reflective Haz-Alert™ hazard labels for easy visibility



Use these cabinets for the safe storage of flammables under fume hoods, benches or counters.



882410



882424



883607

Capacity Gal/L	Doors and Style	Exterior H x W x D	Approv/Lstg Regulation	Yellow Model	Silver Model	Lt Neutral Model	CA Prop 65
15/57	1 door, right hinge, manual	35.75 x 24 x 21.625 in 908 x 610 x 549 mm	FM, O, A, N	882400	882404	882407	
	1 door, left hinge, manual			882410	882414	882417	
	1 door, right hinge, self-close		FM, O, A, N, I	882420	882424	882427	⚠
	1 door, left hinge, self-close			882430	882434	882437	⚠
19/72	2 doors, manual	35.75 x 30 x 21.625 in 908 x 762 x 549 mm	FM, O, A, N	883000	883004	883007	
	2 doors, self-close		FM, O, A, N, I	883020	883024	883027	⚠
23/87	2 doors, manual	35.75 x 36 x 21.625 in 908 x 914 x 549 mm	FM, O, A, N	883600	883604	883607	
	2 doors, self-close		FM, O, A, N, I	883620	883624	883627	⚠
31/117	2 doors, manual	35.75 x 48 x 21.625 in 908 x 1219 x 549 mm	FM, O, A, N	884800	884804	884807	
	2 doors, self-close		FM, O, A, N, I	884820	884824	884827	⚠

Accessories	Fits Cabinet Styles	Dimensions W x D	Model
SpillSlope® steel shelf	15 gallon (57 L)	20.125 x 18 in (511 x 457 mm)	29950
	19 gallon (72 L)	26.125 x 18 in (664 x 457 mm)	29951
	23 gallon (87 L)	32.5 x 18 in (826 x 457 mm)	29949
	31 gallon (117 L)	44.333 x 18 in (1130 x 457 mm)	29953

⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Sure-Grip® EX Flammable Waste Safety Cabinets

- Fire-resistant, fully compliant design for the temporary collection and segregation of flammable liquid waste
- Clearly marked to reduce mix up of contents
- SpillSlope® shelves capture spills in 2-in (51-mm) leakproof sump
- Three-point stainless steel bullet latch for positive closure
- U-Loc™ handle with two keys, accepts optional padlock
- Includes integral vents with flame arresters, built-in grounding connector, and leveling feet



8930053

Capacity Gal/L	Doors	Exterior H x W x D	Shelves	Approv/Lstg Regulation	Model	CA Prop 65
30/114	2 door, manual	44 x 43 x 18 in (1118 x 1092 x 457 mm)	1	FM, N, O, A	8930053	
	2 door, self-close			FM, N, O, A, I	8930253	⚠
45/170	2 door, manual	65 x 43 x 18 in (1651 x 1092 x 457 mm)	2	FM, N, O, A	8945053	
	2 door, self-close			FM, N, O, A, I	8945253	⚠

Sure-Grip® EX Flammable Waste Drum Storage Cabinets

- Safely segregate and temporarily store large quantities of flammable waste
- 18-gauge (1-mm) double-wall, welded steel with 1-1/2-in (38-mm) of insulating air space for fire resistance
- Self-latching doors with 3-point stainless steel bullet latch for secure closure
- Half-depth shelf for extra storage—sized to provide enough space for a drum pump or funnel
- 2-in (51-mm) leakproof sump contains spills
- U-Loc™ handle with two keys, dual vents with flame arresters, built-in grounding connector, and leveling feet



8991053

Drum Capacity Gal/L	Doors and Style	Exterior H x W x D	Shelves	Approv/Lstg Regulation	Model	CA Prop 65
One vertical drum - 55/200	2 door, manual	65 x 34 x 34 in (1651 x 864 x 864 mm)	1	FM, N, O, A	8962053	
	2 door, self-close			FM, N, O, A, I	8962253	⚠
Two vertical drums - 55/200*	2 door, manual	65 x 59 x 34 in (1651 x 1499 x 864 mm)		N, O, A	8991053	

*OSHA 29CFR 1910.106(d)(3) states that not more than 60 gallons (227 L) of Category 1, 2, or 3 flammable liquids, nor more than 120 gallons (454 L) of Category 4 flammable liquids may be stored in a safety cabinet.

Accessories	Fits Cabinet Styles	Dimensions W x D	Model
SpillSlope® steel shelf	30 & 45 gallon (114 & 170 L) - 43 in W (1092 mm)	39.375 x 14 in (1000 x 356 mm)	29937
SpillSlope® half-depth steel shelf	Single vertical 55-gallon (200 L) drum	30.375 x 14 in (771 x 356 mm)	29946
	Double vertical 55-gallon (200 L) drum	55.375 x 14 in (1406 x 356 mm)	29947
Drum roller	Single vertical 55-gallon (200 L) drum	29.5 x 30 in (749 x 762 mm)	25920
	Double vertical 55-gallon (200 L) drum	55.5 x 30 in (1408 x 762 mm)	25922
Drum ramp for all drum cabinets	All drum cabinets	28 x 24.5 in (711 x 622 mm)	25932

⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Sure-Grip® EX Vertical Drum Safety Cabinets

- OSHA- and NFPA-compliant vertical storage for one or two 30- or 55-gallon (110- to 200-L) drums
- 18-gauge (1-mm) double-wall, welded steel with 1-1/2-in (38-mm) of insulating air space for fire resistance
- Half-depth shelf adjusts to accommodate a drum with pump or funnel, or stores spare drum accessories
- Models with drum rollers facilitate the movement of heavy drums; models with removable drum support keeps drum elevated off cabinet sump



Design allows cabinet to be used as a pumping station.

Drum Capacity Gal/L	Style	Includes	Exterior H x W x D	Shelves	Approv/Lstg Regulation	Yellow Model	Red Model	Gray Model	White Model	CA Prop 65
One - 55/200	manual	Drum Support	65 x 34 x 34 in 1651 x 864 x 864 mm	1	FM, N, O, A	896200	896201	896203	896205	
	self-close				FM, N, O, A, I	896220	896221	896223	896225	⚠
Two - 55/200*	manual		65 x 59 x 34 in 1651 x 1498 x 864 mm		N, O, A	899100	899101	899103	899105	
	self-close				N, O, A, I	899120	—	—	—	⚠
One - 55/200	manual	Drum Rollers	65 x 34 x 34 in 1651 x 864 x 864 mm		FM, N, O, A	896260	896261	896263	896265	
	self-close				FM, N, O, A, I	896270	896271	896273	896275	⚠
Two - 55/200*	manual		65 x 59 x 34 in 1651 x 1498 x 864 mm		N, O, A	899160	899161	899163	899165	
	self-close				N, O, A, I	899170	—	—	—	
Two - 30/220	manual	65 x 43 x 34 in 1651 x 1092 x 864 mm	FM, N, O, A	899060	899061	899063	899065			
	self-close		FM, N, O, A, I	899070	899071	899073	899075	⚠		

*OSHA 29CFR 1910.106(d)(3) states that not more than 60 gallons (227L) of Category 1, 2, or 3 flammable liquids, nor more than 120 gallons (454L) of Category 4 flammable liquids may be stored in a safety cabinet.

Sure-Grip® EX Double-Duty Drum Safety Cabinets

- Two separate compartments fit one vertical 55- or 30-gallon (200- or 110-L) drum and up to twelve 5-gallon (19-L) safety cans
- Fully compliant, fire resistant design with three-point, self-latching doors
- Drum area features drum rollers in the sump and one half-depth SpillSlope® shelf
- Can area includes two full-size, adjustable SpillSlope® shelves



Capacity Gal/L	Doors and Style	Exterior H x W x D	Approv/Lstg Regulation	Model
115/435*	2 door, manual with rollers	65 x 59 x 34 in (1651 x 1499 x 864 mm)	N, O, A	899260
	2 door, self-close with rollers		N, O, A, I	899270

*OSHA 29CFR 1910.106(d)(3) states that not more than 60 gallons (227 L) of Category 1, 2, or 3 flammable liquids, nor more than 120 gallons (454 L) of Category 4 flammable liquids may be stored in a safety cabinet.

⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Sure-Grip® EX Horizontal Drum Safety Cabinet

- Fire tested and approved by FM Approvals; 18-gauge (1-mm) double-wall, welded steel
- Holds a horizontally stored 55-gallon (200-L) drum for use in gravity-flow dispensing applications
- Interior provides space for a drip-can and includes tracks to guide drum cradle (sold separately below) into position
- Powder-coat finish, inside and out
- Leakproof, 2-in (51-mm) sump, dual vents with flame arresters
- Built-in grounding connector



899320 (shown with optional cradle 08800)



Use proper grounding techniques when dispensing flammable liquids

Drum Capacity Gal/L	Doors and Style	Exterior H x W x D	Approv/Lstg Regulation	Model	CA Prop 65
One - 55/200	2 door, manual	50 x 30 x 48 in (1270 x 762 x 1219 mm)	FM, N, O, A	899300	
	2 door, self-close		FM, N, O, A, I	899320	⚠

Accessories for Drum Cabinets

- **Cabinet ramp** easily loads a drum into a cabinet using a cart. Ramp fits over the sill to keep securely in place. Tread design on surface maximizes traction. Fits all styles of Justrite drum cabinets. Uniform distributed load limit is 750-lb (340-kg). Not for use with wheeled drum cradle 08800.
- **Drum Roller** for vertical storage cabinet 8962001 (sold separately above) makes it easier to maneuver heavy drums.
- **Wheeled drum cradle** positions a horizontal drum for gravity-flow dispensing.



Ramp side rails provide strength and guidance



08800

Description	Fits Cabinet sizes/UDL	W x D	Model
SpillSlope® half-depth steel shelf	Single vertical 55-gallon (200 L) drum and double-duty 115 gallon (435 L)	30.375 x 14 in (771 x 356 mm)	29946
SpillSlope® steel shelf	Double-duty 115 gallon (435 L)	23 x 29 in (584 x 737 mm)	29974
SpillSlope® half-depth steel shelf	Double vertical 55 gallon (200 L) drum	55.375 x 14 in (1406 x 356 mm)	29947
Drum roller	Single vertical 55 gallon (200 L) drum, UDL 1250 lbs	29.5 x 30 in (749 x 762 mm)	25920
	Double vertical 55 gallon (200 L) drum, UDL 2000 lbs	55.5 x 30 in (1408 x 762 mm)	25922
	Double vertical 30 gallon (114 L) drum, UDL 1250 lbs	37 x 30 in (940 x 762 mm)	25923
Drum ramp for all drum cabinets	All drum cabinets, UDL 750 lbs	28 x 24.5 in (711 x 622 mm)	25932
Drum cradle for single drum	Single horizontal 55 gallon (200 L) drum, UDL 600 lbs	22.5 x 35.5 in (571 x 902 mm)	08800

⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Sure-Grip® EX Classic Safety Cabinets for Combustibles

Separate and identify combustible liquids for safe storage of paints and inks

- Fully compliant, fire tested and approved by FM Approvals
- Sturdy double-wall, 18-gauge (1-mm) steel with 1-1/2-in (38-mm) of insulating air space
- SpillSlope® safety shelves adjust to accept a variety of smaller paint tins and aerosol cans
- Leakproof, 2-in (51-mm) sump captures spills
- 3-point stainless steel bullet latching system for fail-safe closure
- Includes dual vents with flame arresters, adjustable leveling feet, grounding connector



894511

893011

Capacity Gal/L	Doors and Style	Exterior H x W x D	Shelves	Approv/Lstg Regulation	Red Model	Yellow Model	CA Prop 65
20/76	1 door, manual	44 x 23.25 x 18 in (1118 x 591 x 457 mm)	2	FM, N, O, A	891511	891510	
	1 door, self-close			FM, N, O, A, I	891531	891530	⚠
40/151	2 door, manual	44 x 43 x 18 in (1118 x 1092 x 457 mm)	3	FM, N, O, A	893011	893010	
	2 door, self-close			FM, N, O, A, I	893031	893030	⚠
	1 sliding door, self close			FM, N, O, A, I	893091	893090	⚠
60/227	2 door, manual	65 x 43 x 18 in (1651 x 1092 x 457 mm)	5	FM, N, O, A	894511	894510	
	2 door, self-close			FM, N, O, A, I	894531	894530	⚠
	1 sliding door, self-close			FM, N, O, A, I	894591	894590	⚠
96/363*	2 door, manual	65 x 34 x 34 in (1651 x 864 x 864 mm)	5	FM, N, O, A	896011	896010	
	2 door, self-close			FM, N, O, A, I	896031	896030	⚠

*OSHA 29CFR 1910.106(d)(3) states that not more than 60 gallons (227 L) of Category 1, 2, or 3 flammable liquids, nor more than 120 gallons (454 L) of Category 4 flammable liquids may be stored in a safety cabinet.

Accessories	Fits Cabinet Styles	W x D	Model
SpillSlope® steel shelf	20 gallon (76 L) free standing - 23.25 in W (591 mm)	19..625 x 14 in (498 x 356 mm)	29936
	Aerosol can wall mount - 43 in W (1092 mm)	39..375 x 8.625 in (1000 x 219 mm)	29938
	30 & 45 gallon (114 & 170 L) or 40 & 60 gallon (151 & 227 L) - 43 in W (1092 mm)	39..375 x 14 in (1000 x 356 mm)	29937
	60 gallon (227 L) or 96 gallon (363 L) - 34 in W (864 mm)	30.375 x 29 in (771 x 737 mm)	29944

Sure-Grip® EX Wall Mount Cabinet for Aerosol Cans

Store multiple aerosol cans on a wall near workspace for easy access

- Same safety features of Justrite's larger safety cabinets for combustibles
- Mounts on wall to save floor space—comes with mounting hardware
- Depth of 12-in (305-mm) with 3 shelves—holds over 100 aerosol cans

Nom Capacity Aerosol Cans	Doors and Style	Exterior H x W x D	Shelves	Approv/Lstg Regulation	Model
168	2 door, manual	44 x 43 x 12 in 1118 x 1092 x 305 mm	3	FM, N, O, A	8934016



⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Sure-Grip® EX Classic Safety Cabinets for Pesticides

Store agricultural and turf chemicals in indoor maintenance areas of golf courses, parks, nurseries, farms, lawn and pest control companies

- Complies with OSHA and NFPA; FM-approved
- Powder-paint finish, inside and out
- Double-wall, 18-gauge (1-mm) steel with 3-point stainless steel bullet latching system
- Includes two keys—U-Loc™ handle accepts optional padlock for added security
- SpillSlope® steel shelves fitted with polyethylene tray adjust on 3-in (77-mm) centers
- Leakproof 2-in (51-mm) sump, dual vents with flame arresters, adjustable leveling feet, grounding connector
- Thirty-gallon (114-L) models 893004 and 893024 include an additional polyethylene work tray to place on top of the cabinet for a handy work surface



Capacity Gal/L	Doors and Style	Exterior H x W x D	Shelves	Approv/Lstg Regulation	Model	CA Prop 65	
12/45	1 door, manual, compac	35 x 23.25 x 18 in (889 x 591 x 457 mm)	1	FM, N, O, A	891204		
	1 door, self-close, compac			FM, N, O, A, I	891224	⚠	
30/114	2 door, manual	44 x 43 x 18 in (1118 x 1092 x 457 mm)		FM, N, O, A	893004		
	2 door, self-close			FM, N, O, A, I	893024	⚠	
45/170	2 door, manual	65 x 43 x 18 in (1651 x 1092 x 457 mm)		2	FM, N, O, A	894504	
	2 door, self-close				FM, N, O, A, I	894524	⚠
60/227	2 door, manual	65 x 34 x 34 in (1651 x 864 x 864 mm)	FM, N, O, A		896004		
	2 door, self-close		FM, N, O, A, I		896024	⚠	
90/341*	2 door, manual	65 x 43 x 34 in (1651 x 1092 x 864 mm)	FM, N, O, A		899004		
	2 door, self-close		FM, N, O, A, I		899024	⚠	

*OSHA 29CFR 1910.106(d)(3) states that not more than 60 gallons (227 L) of Category 1, 2, or 3 flammable liquids, nor more than 120 gallons (454 L) of Category 4 flammable liquids may be stored in a safety cabinet.

Accessories	Fits Cabinet Styles	W x D	Shelf & Tray Model	Shelf Only Model	Tray Only Model
SpillSlope® steel shelf	12 gallon (45 L) compac	19.625 x 14 in (498 x 356 mm)	29959	29936	29968
	30 & 45 gallon (114 & 170 L) - 43 in W (1092 mm)	39.375 x 14 in (1000 x 356 mm)	29958	29937	29962
	60 gallon (227 L) - 34 in W (864 mm)	30.375 x 29 in (771 x 737 mm)	29980	29944	29961
	90 gallon (341 L) - 43 in W (1092 mm)	39.375 x 29 in (1000 x 737 mm)	—	29945	29972

⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Safety Cabinets for Hazardous Materials

Identify and safely store hazardous materials such as acids, bases, oxidizers, or toxic materials

- Application specific-labels identify contents to safely store and segregate incompatible chemicals
- Double-wall, 18-gauge (1-mm) steel with 1-1/2-in (38-mm) air space; 2-in (52-mm) leakproof sump
- Self-closing door(s) with a 3-point, stainless steel bullet latching system self-latch and self-close
- Fusible link on door(s) melt at 165 F (74 C) for automatic closure under fire conditions
- SpillSlope® adjustable, steel shelves fitted with polyethylene trays for chemical resistance against leaks. Polyethylene liner included for bottom of sump.
- 30-gal (114-L) cabinet includes an extra polyethylene work tray that can be placed on top of cabinet for a handy work surface



Segregate and identify hazardous materials to ensure a safe working environment.



Self-closing mechanism provides obstruction-free access to top shelf space.



Capacity Gal/L	Doors and Style	Exterior H x W x D	Shelves	Approv/Lstg Regulation	Model	CA Prop 65
Classic Safety Cabinets						
30/114	2 door, self-close	44 x 43 x 18 in (1118 x 1092 x 457 mm)	1	FM, H, A, I	863028	⚠
45/170		65 x 43 x 18 in (1651 x 1092 x 457 mm)	2		864528	⚠
60/227		65 x 34 x 34 in (1651 x 864 x 864 mm)			866028	⚠
90/341		65 x 43 x 34 in (1651 x 1092 x 864 mm)			869028	⚠
Countertop Safety Cabinet						
4/15	1 door, self-close	22 x 17 x 17 in (559 x 432 x 432 mm)	1	H, A, I	860428	⚠
Compac Safety Cabinets						
12/45	1 door, self-close	35 x 23.25 x 18 in (889 x 591 x 457 mm)	1	FM, H, A, I	861228	⚠
15/57		44 x 23.25 x 18 in (1118 x 591 x 457 mm)			861528	⚠
Piggyback Safety Cabinets						
12/45	2 door, self-close	18 x 43 x 18 in (457 x 1092 x 457 mm)	0	FM, H, A, I	861328	⚠
17/64		24 x 43 x 18 in (610 x 1092 x 457 mm)	1		861728	⚠
Slimline Safety Cabinets						
22/83 (standard)	1 door, self-close	65 x 23.25 x 18 in (1651 x 591 x 457 mm)	3	FM, H, A, I	862228	⚠
54/204 (deep)		65 x 23.25 x 34 in (1651 x 591 x 864 mm)			865428	⚠
Undercounter Safety Cabinet						
22/83	2 door, self-close	35 x 35 x 22 in (889 x 889 x 559 mm)	1	FM, H, A, I	862328	⚠

Accessories - For extra shelves, see page 30.

⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

ChemCor® Lined Safety Cabinets for Hazardous Materials

Seamless ChemCor® finish protects interior cabinet surfaces from rust and corrosion

- All the same high-performance features of Justrite's Hazardous Material Cabinets with added protection against corrosion from drips and off-gassing from harsh chemicals
- Unique, flame-coated thermoplastic finish on interior doors, shelves, walls, ceiling and sump
- Non-porous, seam-free surface eliminates the need for corrosion-prone rivets or fasteners
- Resists staining and cleans up easily
- 30-gal (114-L) cabinet includes a polyethylene work tray for positioning on top of cabinet as a handy work surface



Label pack includes ten content specific labels.



Capacity Gal/L	Doors and Style	Exterior H x W x D	Shelves	Approv/Lstg Regulation	Model	CA Prop 65
Classic Safety Cabinets						
30/114	2 door, self-close	44 x 43 x 18 in (1118 x 1092 x 457 mm)	1	FM, H, A, I	8630282	⚠
45/170		65 x 43 x 18 in (1651 x 1092 x 457 mm)	2		8645282	⚠
60/227		65 x 34 x 34 in (1651 x 864 x 864 mm)			8660282	⚠
Countertop Safety Cabinet						
4/15	1 door, self-close	22 x 17 x 17 in (559 x 432 x 432 mm)	1	H, A, I	8604282	⚠
Compac Safety Cabinets						
12/45	1 door, self-close	35 x 23.25 x 18 in (889 x 591 x 457 mm)	1	FM, H, A, I	8612282	⚠
Piggyback Safety Cabinets						
12/45	2 door, self-close	18 x 43 x 18 in (457 x 1092 x 457 mm)	0	FM, H, A, I	8613282	⚠
17/64		24 x 43 x 18 in (610 x 1092 x 457 mm)	1		8617282	⚠
Slimline Safety Cabinets						
22/83 (standard)	1 door, self-close	65 x 23.25 x 18 in (1651 x 591 x 457 mm)	3	FM, H, A, I	8622282	⚠
Undercounter Safety Cabinet						
22/83	2 door, self-close	35 x 35 x 22 in (889 x 889 x 559 mm)	1	FM, H, A, I	8623282	⚠

Accessories - For extra shelves, see page 30.

⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Sure-Grip® EX Classic Safety Cabinets for Corrosives

Protect personnel and laboratories from damaging chemicals by storing corrosives in specially designed safety cabinets

- Independently fire tested and approved by FM Approvals
- Powder-coat paint finish, inside and out
- Same fire-resistant design as Justrite cabinets for flammable storage
- Leakproof 2-in (51-mm) sump, dual vents with flame arresters, adjustable leveling feet, grounding connector
- Polyethylene trays fit over galvanized steel SpillSlope® shelves to help resist aggressive chemicals
- Polyethylene liner at bottom of sump removes for easy cleaning of drips and leaks
- Thirty-gal (114-L) models include an additional polyethylene work tray to place on top of the cabinet for a handy work surface



894502



893002



Safely store corrosives in fire-resistant steel safety cabinets.

Capacity Gal/L	Doors and Style	Exterior H x W x D	Shelves	Approv/Lstg Regulation	Model	CA Prop 65
30/114	2 door, manual	44 x 43 x 18 in (1118 x 1092 x 457 mm)	1	FM, A9	893002	
	2 door, self-close				893022	⚠
	1 bi-fold sliding door, self-close				893082	⚠
	2 door, manual				893302	
45/170	2 door, manual	65 x 43 x 18 in (1651 x 1092 x 457 mm)			894502	
	2 door, self-close				894522	⚠
	1 bi-fold sliding door, self-close				894582	⚠
60/227	2 door, manual	65 x 34 x 34 in (1651 x 864 x 864 mm)	2	FM, A9	896002	
	2 door, self-close				896022	⚠
	1 bi-fold sliding door, self-close				896082	⚠
90/341	2 door, manual	65 x 43 x 34 in (1651 x 1092 x 864 mm)			899002	
	2 door, self-close				899022	⚠
	1 bi-fold sliding door, self-close				899082	⚠

Accessories - For extra shelves, see page 30.

⚠ **WARNING:** This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Sure-Grip® EX Slimline Safety Cabinets for Corrosives

Compact footprint offers versatile storage options

- Same safety features as Justrite's larger corrosive safety cabinets, in a footprint that fits the tightest spaces
- Independently fire tested and approved by FM Approvals
- Modular size fits nicely alongside existing safety cabinets to expand storage capacity
- Includes polyethylene trays that fit on top of three galvanized steel SpillSlope® safety shelves



Capacity Gal/L	Doors and Style	Exterior H x W x D	Shelves	Approv/Lstg Regulation	Model	CA Prop 65
22/83 (standard)	1 door, manual	65 x 23.25 x 18 in (1651 x 591 x 457 mm)	3	FM, A9	892202	
	1 door, self-close			FM, A9	892222	⚠
54/204 (deep)	1 door, manual	65 x 23.25 x 34 in (1651 x 591 x 864 mm)		FM, A9	895402	
	1 door, self-close			FM, A9	895422	⚠

Sure-Grip® EX Countertop and Compac Safety Cabinets for Corrosives

Make the most of your available space

- Keep your most frequently used fluids close at hand
- Same safety features as Justrite's larger size corrosive safety cabinet, for use on countertop or free-standing for smaller quantities of corrosives
- Baked-on blue epoxy powder-coat finish to resist acids, bases, and solvents
- Steel shelves include polyethylene liner and a separate polyethylene liner at bottom sump that removes for easy cleaning



Capacity Gal/L	Doors and Style	Exterior H x W x D	Shelves	Approv/Lstg Regulation	Model	CA Prop 65
4/15	1 door, manual, countertop	22 x 17 x 17 in (559 x 432 x 432 mm)	1	A9	890402	
	1 door, self-close, countertop			A9	890422	⚠
12/45	1 door, manual, compac	35 x 23.25 x 18 in (889 x 591 x 457 mm)		FM, A9	891202	
	1 door, self-close, compac			FM, A9	891222	⚠
15/57	compac; 1 door manual	44 x 23.25 x 18 in (1118 x 591 x 457 mm)	FM, A9	891502		
	compac; 1 door self-close		FM, A9	891522	⚠	

Accessories - For extra shelves, see page 30.

⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Sure-Grip® EX Piggyback Safety Cabinets for Corrosives

Use on bench tops or add to taller cabinets to meet increased storage need

- Safely store acids or bases without taking up additional floor space—fits on top of 30- and 45-gallon (114- and 170-L) manual or self-closing Sure-Grip® EX cabinets
- Compact design permits stacking of piggyback cabinets, or use optional wall hanger assembly No. 25950 to mount cabinet to wall
- Complies with OSHA and NFPA; FM-approved
- Double-wall, 18-gauge (1-mm) steel with 3-point stainless steel bullet latching system
- Leakproof 2-in 51-mm) sump, dual vents with flame arresters, adjustable leveling feet, grounding connector



Expand storage capacity by mounting piggyback cabinet on top of Justrite's 30- or 45-gallon cabinet.



891702 stacked



891722



891302

Capacity Gal/L	Doors and Style	Exterior H x W x D	Adjustable Shelves	Approv/Lstg Regulation	Model	CA Prop 65
12/45	2 door, manual	18 x 43 x 18 in (457 x 1092 x 457 mm)	0	FM, A9	891302	
	2 door, self-close				891322	⚠
17/64	2 door, manual	24 x 43 x 18 in (610 x 1092 x 457 mm)	1		891702	
	2 door, self-close				891722	⚠

Accessories—see page 36.

⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Sure-Grip® EX Undercounter Safety Cabinets for Corrosives

Safely store corrosives near point-of-use under lab counters for quick and easy access

- Powder-coat finish—inside and out for chemical resistance
- Fire-tested and approved by FM Approvals
- Same benefits as Justrite’s flammable storage cabinets— with the addition of polyethylene trays on top of galvanized SpillSlope® steel shelves for added resistance against damaging corrosive drips and leaks
- Leakproof 2-in (51-mm) sump includes a polyethylene sump liner that removes for easy cleaning
- Toe kick offers improved ergonomics allowing user to stand closer to counter—less leaning



Self-latching doors include paddle handle with cylinder lock.

Capacity Gal/L	Doors and Style	Exterior H x W x D	Shelves	Approv/Lstg Regulation	Model	CA Prop 65
22/83	2 door, manual	35 x 35 x 22 in (889 x 889 x 559 mm)	1	FM, A9	892302	
	2 door, self-close			FM, A9	892322	⚠

Accessories for dark blue hazardous material cabinets or light blue corrosive storage cabinets

- Galvanized steel shelves hold up to 350 lb (159 kg) and adjust on 3-in (76-mm) centers
- Polyethylene trays fit over steel shelves for added corrosion protection against leaks when storing damaging corrosive liquids
- Available options include: combination tray with poly tray, steel shelf alone, or poly tray alone
- Use optional wall hanger assembly on smaller cabinets when wall mounting is desirable—comes in two sizes



Description	Fits Cabinet Styles	W x D	Shelf & Tray Model	Shelf Only Model	Tray Only Model
SpillSlope® steel shelf	4 gallon (15 L) countertop	13.375 x 13 in (340 x 330 mm)	29973	29935	25934
	12 & 15 gallon (45 & 57 L) compac 22 gallon (83 L) slim	19.625 x 14 in (498 x 356 mm)	29959	29936	29968
	22 gallon (83 L) undercounter	31.556 x 18 in (802 x 457 mm)	29960	29939	29965
	17, 30 & 45 gallon (64, 114 & 170 L) - 43 in W (1092 mm)	39.375 x 14 in (1000 x 356 mm)	29958	29937	29962
	54 gallon (204 L) deep slimline	19.625 x 29 in (498 x 737 mm)	—	29941	29907
	60 gallon (227 L) - 34 in W (864 mm)	30.375 x 29 in (771 x 737 mm)	29980	29944	29961
	90 gallon (341 L) - 43 in W (1092 mm)	39.375 x 29 in (1000 x 737 mm)	—	29945	29972
Wall mount kit	4 gallon (15 L) countertop	—	25951	—	—
	12 & 17 gallon (45 & 64 L) piggyback		25950		
Tray for cabinet top	17, 30 & 45 gallon (64, 114 & 170 L) - 43 in W (1092 mm)	43.5625 x 18.5625 in (1106 x 471 mm)	—		25933

Description	W x D	Model
Label pack (replacement/retrofit) with "Hazardous—Keep Fire Away" warning and 10 content ID labels	—	29017
Single label: "Lithium-Ion Battery Storage Cabinet"	12 in W x 3.5 in H (305 x 89 mm)	29018

⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

ChemCor® Lined Safety Cabinets for Corrosives

100% seamless thermoplastic coating inside the cabinet provides superior corrosion protection combined with fire protection in a single cabinet

- Nonporous thermoplastic coating lines insides
- Specifically formulated powder-coat finish on exterior provides long life and extra resistance to deterioration from harsh chemicals
- Seam-free surfaces resists stains and clean easily
- Includes two labels to be placed on cabinet – “Base” or reflective Haz-Alert™ “Acid”
- Double-wall, 18-gauge (1-mm) steel with 3-point stainless steel bullet latching system
- Leakproof 2-in (51-mm) sump, dual vents with flame arresters, adjustable leveling feet, grounding connector



See next page for models in a variety of styles.



8831022



8837272



8849022

ChemCor® Lined Under Fume Hood Acid Cabinets

Capacity Gal/L	Doors and Style	Exterior H x W x D	Shelves	Approv/Lstg Regulation	Silver Model	Blue Model	Lt Neutral Model	CA Prop 65
15/57	1 door, right hinge, manual	35.75 x 24 x 21.625 in 908 x 610 x 549 mm	1	FM, A9	8825042	8825022	8825072	
	1 door, left hinge, manual				8825142	8825122	8825172	
	1 door, right hinge, self-close				8825242	8825222	8825272	▲
	1 door, left hinge, self-close				8825342	8825322	8825372	▲
19/72	2 door, manual	35.75 x 30 x 21.625 in 908 x 762 x 549 mm	1	FM, A9	8831042	8831022	8831072	
	2 door, self-close				8831242	8831222	8831272	▲
23/87	2 door, manual	35.75 x 36 x 21.625 in 908 x 914 x 549 mm	1	FM, A9	8837042	8837022	8837072	
	2 door, self-close				8837242	8837222	8837272	▲
31/117	2 door, manual	35.75 x 48 x 21.625 in 908 x 1219 x 549 mm	1	FM, A9	8849042	8849022	8849072	
	2 door, self-close				8849242	8849222	8849272	▲

ChemCor® Lined Safety Cabinets for Corrosives



ChemCor® Lined Acid Cabinets - Free Standing

Capacity Gal/L	Doors and Style	Exterior H x W x D	Shelves	Color	Approv/Lstg Regulation	Model	CA Prop 65
30/114	2 door, manual	44 x 43 x 18 in 1118 x 1092 x 457 mm	1	Blue	FM, A9	8930022	
	2 door, self-close					8930222	⚠
	1 bi-fold sliding, self-close					8930822	⚠
45/170	2 door, manual	65 x 43 x 18 in 1651 x 1092 x 457 mm	2	Blue	FM, A9	8945022	
	2 door, self-close					8945222	⚠
	1 bi-fold sliding, self-close					8945822	⚠
60/227	2 door, manual	65 x 34 x 34 in 1651 x 864 x 864 mm				8960022	
	2 door, self-close					8960222	⚠
Slimline Safety Cabinets							
22/83	1 door, manual	65 x 23.25 x 18 in 1651 x 591 x 457 mm	3	Blue	FM, A9	8922022	
	1 door, self-close					8922222	⚠
Countertop and Compac Safety Cabinets							
4/15	1 door, manual, countertop	22 x 17 x 17 in 559 x 432 x 432 mm	1	Blue	A9	8904022	
	1 door, self-close, countertop					8904222	⚠
12/45	1 door, manual, compac	35 x 23.25 x 18 in 889 x 591 x 457 mm			FM, A9	8912022	
	1 door, self-close, compac					8912222	⚠
Undercounter Safety Cabinets							
22/83	2 door, manual	35 x 35 x 22 in 889 x 889 x 559 mm	1	Blue	FM, A9	8923022	
	2 door, self-close					8923222	⚠
Piggyback Safety Cabinets							
12/45	2 door, manual	18 x 43 x 18 in 457 x 1092 x 457 mm	0	Blue	FM, A9	8913022	
	2 door, self-close					8913222	⚠
17/64	2 door, manual	24 x 43 x 18 in 610 x 1092 x 457 mm	1			8917022	
	2 door, self-close					8917222	⚠

Accessories	Fits Cabinet Styles	W x D	Model
ChemCor® SpillSlope® steel shelf	15 gallon (57 L) under fume hood	20.125 x 18 in (511 x 457 mm)	29934
	19 gallon (72 L) under fume hood	26.125 x 18 in (664 x 457 mm)	29930
	23 gallon (87 L) under fume hood	32.5 x 18 in (826 x 457 mm)	29940
	31 gallon (117 L) under fume hood	44.333 x 18 in (1130 x 457 mm)	29948

⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Polyethylene Cabinet for Corrosive Chemicals


Completely metal-free poly cabinet—never worry about rust again

- For strong acids such as hydrochloric, sulfuric, or nitric acid; or bases such as sodium, potassium, or calcium hydroxide
- Durable HDPE (high-density polyethylene) for chemical resistance
- Shelf adjusts on 3-in (76-mm) increments with a load capacity of 125-lbs (57-kgs)
- Removable sump cover serves as a bottom shelf, concealing the integrated, 8.5-gal (32-L capacity) leakproof sump
- Door accepts optional padlock
- Use for stand-alone storage for access to grooved top surface
- When used under a counter, recessed toe kick provides improved ergonomics
- Four pre-formed, rear vent locations provide a guide for an aftermarket vent kit (not included) if a pressurized vapor removal system is required
- Expand capacity by stacking two cabinets



Free-standing safe storage for harsh acids, or use undercounter for convenient access.

3 application specific labels provide for segregation of chemicals included on both cabinet styles.



Description	Capacity	Doors	Exterior H x W x D	Shelves	Shelf Load lb/kg	Model
Stand-alone polyethylene cabinet	Thirty-six, 2.5-liter bottles	2 door	35 x 36 x 25 in (889 x 914 x 635 mm)	1	125/57	24180
Replacement polyethylene center shelf for 24180	—	—	33.375 W x 20.375 D in (848 W x 518 D mm)	—	125/57	24103

Countertop Polyethylene Cabinet for Corrosives

- Point-of-use convenience for small quantities of acids or bases
- Completely metal-free—excellent chemical resistance against damaging spills or vapors
- Includes two poly shelves; use one inside to catch leaks, store the other under cabinet and remove for use as a worktop
- Hinge door from either side—accepts optional padlock



Compact design offers placement on lab counters for access to frequently used chemicals.

Description	Capacity	Doors	Exterior H x W x D	Shelves	Shelf Load lb/kg	Model
Countertop polyethylene cabinet	Two, 4-liter bottles	1 door	19.75 x 14.25 x 17.125 in (502 x 362 x 435 mm)	—	—	24080

Wood Laminate Acid Cabinets

- Long lasting wood construction with stainless steel handles and hinges
- Shelf adjusts on 1-1/4-in (32-mm) centers
- Includes adjustable leg levelers, Haz-Alert™ reflective labels, and double key set
- Undercounter model 24140 includes a removable, easy-to-clean polyethylene work surface that is recessed 5/8-in (16-mm) to contain leaks



Capacity	Number of Doors and Style	Exterior H x W x D	Shelves	Model
Six, 2.5 liter bottles	2 door, countertop	18.5 x 24 x 16 in (470 x 610 x 406 mm)	0	24120
Thirty-six, 2.5 liter bottles	2 door, stand alone	35.75 x 36 x 22 in (908 x 914 x 559 mm)	1	24140
Forty-nine, 2.5 liter bottles		60 x 42 x 17.875 in (1524 x 1067 x 454 mm)		24150

24140 height dimension includes 0.75-in (19-mm) top. For undercounter usage, remove top for 22-in (559-mm) depth and adjust leg levelers which extend up to 0.75-in (19-mm).

Accessories	Exterior W x D	Model
Wood shelf and clips for 24140	34 x 16.875 in (864 x 429 mm)	24168
Wood shelf and clips for 24150	40 x 13.875 in (1016 x 352 mm)	24167

Solid Polyethylene Acid Cabinets

- Suitable for highly aggressive liquids—no metal parts to corrode
- Leakproof 2-in (51-mm) sump
- Three-point door latch on larger units offer secure closure
- Shelf on larger units adjust on 3-in (76-mm) centers
- Door accepts optional padlock
- Toe kick on undercounter model offers improved ergonomics—less leaning



Capacity	Doors and Style	Exterior H x W x D	Shelves	Model
Six, 2.5 liter bottles	1 door, countertop	22 x 17 x 17 in (559 x 432 x 432 mm)	–	24004
Thirty-six, 2.5-liter bottles	2 door, undercounter	35.75 x 36 x 21.75 in (908 x 914 x 552 mm)	1	24010
Thirty-six, 2.5-liter bottles	2 door, stand alone	36.75 x 36 x 21.75 in (933 x 914 x 552 mm)		24015

Accessories	Fits Cabinet Sizes	W x D	Model
Solid polyethylene shelf with shelf pegs	36 in (914mm) W	34.75 x 20.5 in (883 x 521 mm)	24115

Document Storage Boxes

Keep your important papers readily available while protecting them from moisture and dirt

- Weather-resistant polyethylene storage boxes safely store manuals and documents
- Bright red color for visibility with smooth area that accepts ID label
- Label pack includes 2 blank labels and 2 printed labels (SDS and Instruction Manual)
- Includes heavy-duty double-sided tape for easy installation
- Large size accepts SDS binder; medium and large sized boxes accept padlock

Ideal for storage of safety data sheets, instruction sheets, receiving bills, evacuation plans, schedules, plant layouts, inventory checklists, operator manuals, emergency contacts, certificates, and medical records.



Double sided tape is provided for mounting on surfaces that should not be penetrated by hardware such as safety cabinets.



Description	Approx Interior H x W x D	Exterior H x W x D	Lock Hole Dia	Single Unit Model	Master Carton Packs	
Medium top opening	11.5 x 8.75 x 1.625 in (292 x 222 x 41mm)	12.5 x 10.25 x 2.25 in (318 x 260 x 57 mm)	0.25 in/6 mm	S23303	20	23303
Medium front opening	12.25 x 8.625 x 1 in (311 x 219 x 25 mm)	14.5 x 11 x 2.125 in (368 x 279 x 54 mm)	0.375 in/10 mm	S23304		23304
Tube twist-on lid	12 x 3 dia in (305 x 76 dia mm)	12.5 x 3.75 OD in (318 x 94 OD mm)	—	S23305		23305
Large front opening	13.25 x 10.75 x 2.25 in (337 x 273 x 57 mm)	15.75 x 13.125 x 3.625 in (400 x 333 x 90 mm)	0.375 in/10 mm	S23306	10	23306
Label pack (4 yellow labels: 2 blank and 2 printed - SDS and instruction manual)				—	20	23310

VaporTrap™ Safety Cabinet Filter

Improves your work environment by reducing employee's inhalation exposure to VOC's

- Reduce harmful volatile organic chemical vapors inside your safety cabinet
- Activated carbon filter medium contained in a stainless steel mesh cartridge adsorbs VOC vapors
- Magnetized base offers flexible placement anywhere within the cabinet
- Date notation area on label serves as a reminder for replacement—life cycle varies based upon vapor types and concentrations



Note: Due to variables such as the chemical itself, its purity, or its vapor pressure, temperature, humidity, charcoal age, etc., it is difficult to estimate VOC vapor adsorption rates. The Justrite VaporTrap™ Carbon Filter is not intended to be used as a substitute for using safe closed containers as required by OSHA and the EPA. It is important to clean up spills and residues from the cabinet and containers.



For increased safety, position one or two VaporTrap™ Filters inside the cabinet.

Description	Nom. Dimensions Filter L x D	Model
VaporTrap™ filter (2 pk.)	8.75 x 2.25 in (222 x 57 mm)	29916

Safety Cabinet Accessories

Accessories offer organization and convenience

Steel Shelf Dividers fit all Justrite cabinets with 14-in (355-mm) deep shelves. Simply place over shelf and slide into position as desired.

Seismic Bracket Kit provides increased stability—ideal for earthquake or hurricane prone areas. One kit secures any safety cabinet to a wall or floor. Because there are no holes created, the fire protection properties of the cabinet remain intact and the cabinet maintains FM approval.

Leg Riser Frame provides sturdy, stable support for easy relocation of empty cabinet with forklift or pallet jack. High leg frame makes it easy to clean underneath and keeps cabinet away from floor moisture. Includes leg levelers and safety warning label: “Forklift Only When Empty”.

Rolling Cart makes it easy to move a heavy safety cabinet—transport solvents and chemicals directly to your work area. All welded 1/8-in (3-mm) thick heavy-duty steel and 5-in (127-mm) poly caster wheels with brakes for added safety. Push handle is removable. Fits any cabinet 43-in W x 18-in D (1092-mm x 457-mm) with a maximum height of 44-in (1118-mm).



29985 - Set of 4



84000



84001



84002

Description	Load Capacity lb/kg	H x W x D	Model
Shelf dividers for 30G/114L, 40G/151L, 45G/170L, 12G/45L & 15G/57L compac, 22G/83L slimline and 17G/64L piggyback	—	2 x 2.031 x 14.171 in (51 x 52 x 360 mm)	29985
Shelf dividers for 22G/83L undercounter	—	2 x 2.031 x 18.171 in (51 x 52 x 462 mm)	29990
Leg riser frame for 30G/114L and 45G/170L and fume hood cabinets 19G/72L, 23G/87L, 31G/117L	1000/454	5.25 x 43.75 x 18.75 in (133 x 1111 x 476 mm)	84002
Rolling cart for 30G/114L and piggyback style	500/227	42 x 43.25 x 18.25 in (1066 x 1099 x 464 mm)	84001
Seismic bracket kit fits all cabinet sizes	—	4 x 48 x 4 in (102 x 1219 x 102 mm)	84000