

Leak sealing bags for cracks TV

Leak sealing bags for cracks are used for quick and temporary sealing of damaged cisterns, tanks and barrels. This is done by attaching the bag by tensioning belts and its inflation.

Type		TV 23/23	TV 60/30 - 1,5	TV 60/30 - 8	TV 60/30 O
Product number		1901	1908	1905	1909
Dimensions	mm	230 x 230	620 x 300	620 x 300	620 x 300
Max. sealing area	mm	200 x 200	500 x 250	500 x 250	500 x 250
Operating pressure	MPa	0,15	0,15	0,8	0,15
Sealing pressure	MPa	0,14	0,14	0,7	0,14
Weight	kg	1,5	6	6	10

Accessories:

- 50153 Tensioning and extensioning belt with ratchet 5 m
- 50154 Tensioning and extensioning belt with ratchet 10 m
- 50650 Tensioning and extensioning belt with ratchet 10 m
- 2020 Sealing plate 230 x 230 mm
- 2021 Sealing plate 500 x 300 mm
- 2144 Inflation hose with chain and nipple 10 m
- 2039 Safety and control gauge 0,15 MPa - V 1,5
- 2146 Safety and control gauge 0,8 MPa - V 8
- 2145 Acid proof protection bag, PVC
- 2143 Foot pump 0,6 MPa

